

RGPC 800 RM Pro

Parallel Power Delivery for
Load Impedance matching

Features

The RGPC 800 RM Pro is designed for installations where the ratio of space/performance is at premium. Its Parallel Delivery Choke Technology is specifically designed to fit into a 2U rack space, With four duplex outlets on the back, it is capable to power most midsized home theater systems. To receive the maximum performances install the RGPC 800 RM Pro as close as possible to the AV equipment.

The RGPC 800 RM Pro, utilizes Balanced Surge Protection Design (SPD) to ensure Bidirectional Protection and Reduced Ground Interference.

Features & Benefits

- High Current on Demand
- 8 5-20R outlets
- Balanced AC Surge Protection
- Resettable Circuit Breaker
- Compatible with UL1449 3rd edition for Type 3 locations

Applications

- All AV equipment
- Midsized Home Theaters
- Installations with Multiple Circuits
- Home Automation
- Home Integration
- For Crisp and Flawless AV Experience



Specs:

	800 RM Pro 120/120	800 RM Pro 240/240
Dimensions (WHD)	17 x 3.5 x 11	17 x 3.5 x 11
Net weight	32 lbs	32 lbs
Rack Mountable	Yes, rack ears included	Yes, rack ears included
Power Cord Low Impedance (detchble)	6 ft, 12 AWG, NEMA 5-15P	6 ft, 12 AWG, Euro Schuko Plug
Outlets	8 5-20R	8 5-20R
Input Voltage	120 VAC	240 VAC
Output Voltage	120 VAC	240 VAC
Frequency	60 HZ	50 HZ
Output Power	12 A (1,440 Watts)	12 A (2,880 Watts)
Technology	Parallel Power Delivery	Parallel Power Delivery
Indicator Light	Blue LED	Blue LED
AC Surge Protection (type 3 locations)	Balanced	Balanced
Efficiency	99%	99%
Cooling	Convectional	Convectional
Storage Temperature	-40° C to 85° C	-40° C to 85° C
Operating Temperature	-40° C to 65° C	-40° C to 65° C

